

## Planar QE8650-T

Interactive 4K LCD Display

The Planar® QE8650-T display connects a multitouch experience with stunning 4K image clarity. Offering an affordable solution for professionals who seek to collaborate or annotate using a large viewing area, Planar QE8650-T delivers the highest image resolution and enterprise-level features in conference rooms or huddle spaces, and is also ideal for public display applications such as way-finding, product catalogs and any interactive digital signage designed to promote customer engagement. The Planar QE8650-T offers 20 points of multi-touch and multiuser technology, making it easy for multiple users to collaborate and interact at the same time.



| SPECIFICATION                   | DETAIL   |
|---------------------------------|--|
| Product Name                    | Planar QE8650T   |
| Planar Part Number              | 997-8798-01  |
| Display Resolution              | Ultra HD (3840 x 2160)   |
| Screen Size                     | 86 in. (diagonal)  |
| Aspect Ratio                    | 16:9   |
| Display Active Area             | 74.6" x 42.0" (1895mm x 1066mm)  |
| Cabinet Dimensions (W x H x D)  | 77.1" x 44.4" x 3.7" (1957mm x 1128mm x 95mm)  |
| Bezel Width                     | 1.2" (31.0mm) left/right, top/bottom   |
| Brightness (w/protective glass) | 475 nits   |
| Response Time (typ)             | 6 ms   |
| Frame Rate                      | 120Hz  |
| Contrast Ratio (typ)            | 1200:1   |
| Contrast Ratio - Dynamic        | 20,000:1   |
| Viewing Angle (typ)             | 178°   |
| Color Gamut                     | 72% NTSC   |
| Display Color                   | >1 billion colors. Full 10 bit data path   |
| Modes                           | 3840x2160 @ 24/25/30/60Hz; 1920x1080 @ 24/25/30/50/60Hz; 480p, 576p, 720p @ 50/60 Hz; 1080p @ 24/25/30/50/60Hz; 1080i @ 50/60 Hz |
| Pixel Pitch                     | 0.429 mm   |
| Weight                          | 158 lbs (72 kg)  |

| Backlight                   | LED   |
|-----------------------------|---|
| Line Voltage                | 100-240V; 50/60Hz   |
| Power Consumption (typ)     | 165W (standby: <1W)   |
| Operating Temperature       | 0° to +35°C (32° to 95°F) at up to 1500m, 0° to +30°C (32° to 86°F) at up to 3000m  |
| Humidity                    | 20 - 85% RH (non-condensing)  |
| Approvals                   | FCC Class A, cTUVus, RoHS   |
| <b>External Connections</b> | DisplayPort 1.2 x 1, HDMI 2.0 x 2 (HDCP 2.2), HDMI 1.4 x 2  |
| Audio Output                | PC Line Out, S/PDIF   |
| Multi-Source Views          | Quad only   |
| Display Control             | IR, RS-232, LAN, Keypad   |
| Speakers                    | 10W x 2 built-in  |
| Orientation                 | Landscape/Portrait  |
| Mounting                    | VESA: 600 x 400 mm  |
| Fanless                     | Yes   |
| HD format                   | 4K UHD 2160p  |
| Touch Technology            | IR 20 point touch   |
| OS Compatibility            | Windows 7, 8, 10, Mac OSX and Linux   |
| Display Technology          | Edge-lit LED LCD  |
| Recommended Usage           | Up to 24x7 operation  |
| Warranty                    | 3 years Advance Exchange  |
| Options / Features          | TAA compliant   |
| In the Box                  | QE8650T display, power cord, IR sensor, USB (A to B) cable, remote control, TouchMark license key (one time download) and USB drive containing User Manual, touch drivers, and USB-to-serial driver |
| UPC                         | 8 10689 00740 1   |

Specifications are subject to change without notice.

Specification Report Date: 11/30/2021

© Copyright 2021 Planar Systems, Inc. All rights reserved