

Professional IP Monitor – IP Series


- CH-L320-3HDVSB-IP32

Special features

- H264 compression format
- VGA/ DVI-D and Full HD Input
- Real-time display
- Graphical and text interfaces (GUI)
- Use Ethernet connection control
- Support HDMI video output (1920 x 1080 @30)
- Supports up to four network cameras via HUB
- Supports network protocols TCP/IP, DHCP, DNS, HTTP, SMTP



Monitor Connection



Specifications

Model	CH-L320-2HDVS-IP16
LCD panel	32"
Visible area (mm)	698.4 x 392.8
Picture format	16 : 9
Max. resolution	1920 x 1080
Pixel dot pitch (mm)	0.36375x 0.37375
Colours	16.7M
Brightness	350 cd/m ² [LED]
Contrast	3000:1
Response time(Tr/Tf)	8ms
View angle (U/D/L/R)	89/89/89/89
Full HD input	1x Full HD
Audio input(R/L)	2x (RCA)
PC input	1x VGA input 1x DVI-D input
Earphone out	1xPhone jack ,3.5ψ
Speaker	2x built-in speaker (2 watt)
IP Video support	32CH(2592x1944) / 25CH(2592x1944) 16CH(3840x2160) / 8CH(3840x2160) / 4CH(3840x2160)
OSD setting	Yes
Network Port	1x RJ45, 10M/100M
USB Port	2x USB 2.0 ports
HDD Port	1x e-SATA port
Power input	AC 100-240V 50/60Hz
Power consumption	Approx. 58 watt
Dimensions (WxHxD) mm	761.6 x 454.6 x 93.2
Weight	13.2 kg
Operating temperature	0° to 40° C

Subject to technical changes without prior notice. Error excepted.